

# WASTAMAS CSS SDN. BHD.

## FLOAT OPERATED MECHANICAL LEVEL INDICATOR



### INTRODUCTION

**Wastamas** float operated mechanical level indicators are reliable and cost effective mechanical instruments. Their casing is made of robust weatherproof material that makes them suitable to use for outdoor mounting like top of reservoirs, water tanks, pump sump, channel and etc.

### FEATURES

All internal parts are made from non-corrosive materials for optimum weather resistance, this also makes it easy to maintain. Its contrasting level markings enable the indication to be viewed from far away with ease.

### MOUNTING

Due to the nature of design, the indicators are suitable to be installed above water levels that required to be measured. However the large dial surface up to 900mm diameter enable the readings to be viewed from far distance.

### SPECIFICATION

Indicator dial size : 600mm, 900mm diameter  
Level range : 0-3 m, 0-4 m, 0-5m, 0-6 m, 0-8 m, 0-10 m  
Working temperature : 10°C to 70°C (50°F to 160°F)  
Relative humidity : 90 % RH  
Accuracy : ± 5 %

#### Material of construction:

Casing : Mild steel coated with corrosion resistant paint  
Gears : Teflon, bronze or stainless steel  
Float : PVC or stainless steel  
Bolts & Nuts : Stainless steel  
Glass panel : Tempered glass



**WASTAMAS CSS SDN BHD** (711759-P)

NO. 7, JALAN INDUSTRI USJ 1/7, TAMAN PERINDUSTRIAN USJ 1,  
47600 SUBANG JAYA, SELANGOR DARUL EHSAN, MALAYSIA.

TEL : 603-8023 8011 FAX : 603-8023 8022

E-MAIL : sales@wastamas.com